

P60E

Modular electric oven for pizzeria

COMPOSITION WITH 2 BAKING CHAMBERS



OPTIONS AND ACCESSORIES (WITH SURCHARGE)

- ☐ Leavening prover on wheels, height 800mm
- Leavening prover on wheels, height 600mm
- ☐ Support with wheels, height 600mm
- ☐ Support with wheels, height 800mm
- Additional tray holder guides for compartment and support
- Suction hood

(WITHOUT SURCHARGE)

☐ Front vapour collection hood in stainless steel sheet

EXTERNAL CONSTRUCTION

- ☐ Structure made in folded stainless steel
- ☐ Side panels in pre-painted sheet metal
- ☐ Stainless steel hood with aluminised steel top cover
- ☐ Front vapour collection hood in enameled steel sheet
- Steam duct in stainless steel plate
- ☐ Stainless steel door with bottom hinge and spring balance
- ☐ Tempered glass element
- ☐ Handles in thermoplastic material
- ☐ Control panel on front right hand side

INTERNAL CONSTRUCTION

- □ Refractory brick cooking surface
- ☐ Aluminated steel top and side structure
- ☐ Rock wool heat insulation

FUNCTIONING

- ☐ Heated by armoured heating elements
- ☐ Electronic temperature management with independent adjustment of ceiling and floor
- Maximum temperatura reached 450°C
- ☐ Continuous temperature monitoring with thermocouple
- Vapour ducting using manual butterfly valve

STANDARD EQUIPMENT

- ☐ Lighting with halogen lamp
- ☐ Timer
- □ Economiser
- ☐ Independent maximum temperature safety device
- 20 customisable programs




MORETTI FORNI S.P.A.

www.morettiforni.com marketing@morettiforni.com Via A.Meucci, 4 - 61037 Mondolfo (PU) ITALIA Tel. +39.0721.96161 - Fax +39.0721.9616299



P60E 2 baking chambers height 18cm

(assembled with support height 800mm)



Nota: The dimensions indicated in the views are in millimetres. Steamer for Bakery only.

SPECIFICATIONS

The appliance comprises two independent cooking elements and an optional leavening compartment or support. The oven cooking surface is made of refractory, allowing pefect heat distribution over the whole surface and making this oven particularly suitable for use by pizza cooks. Temperature adjustment is electronic, with independent control of the ceiling and floor heating elements. The oven door is hinged at the bottom, with a tempered glass window to check the state of the product while it is cooking. The support comprises a painted metal structure, whereas the leavening compartment has a stainless steel structure and is fitted with a heating thermostat. The leavening compartment can reach a maximum temperature of 65°C, whereas the maximum temperature of the baking chamber is 450°C

All the data provided below refer to the configuration with 2 baking chambers

DIMENSIONS		SHIPPING INFORMATION	FEEDING AND POW	FEEDING AND POWER	
External height	1090mm	Packed in wooden crate	Standard feeding		
External depth	1541mm	Height 12	240mm A.C. V400 3N		
External width	970mm	Depth 17	741mm Feeding on request		
Weight	303kg	Width 11	170mm A.C. V230 3		
Baking surface	1m ²	Weight (303	+60)kg Frequency	50/60Hz	
_		-	Max power	15,8kW	
TOTAL BAKING CAPACIT	′	When combined with leaver	ning *Average power cons	8kWh	
		compartment or support:	Connecting cable for e	each chamber	
Tray (600x400)mm	4	Max height 22		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
		Max weight (377	(+70)kg 5x4mm ² (V	5x4mm ² (V400 3N)	
Pizza diameter 300mm	8	-	4x6mm ² (V	4x6mm ² (V230 3)	
Pizza diameter 450mm	2		Power supply (options	Power supply (optional prover)	
			A.C. V230 1N 50/60 I	A.C. V230 1N 50/60 Hz	
			Max power	1,5kW	
			*Average power cons	0,8kWh	
			Conn. Cable typ	e H07RN-F	
			3x1,5mm ²		

^{*} This value is subject to variation according to the way in which the equipment is used

⁻ NOTE: MORETTI FORNI S.P.A. reserves the right to modify the characteristics of the products illustrated in this publication without prior notice