

VEE RAY SINGLE PAN GAS FRYER 450mm

GT45

- High performance single pan fryer
- Patented infra-red burner system
- Easy clean stainless steel open pan with 10 year limited warranty
- 20L oil capacity
- Large capacity cool zone
- 32mm (1 ¹/₄") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Vitreous enamelled front panel
- \bullet 32mm (1 $^{1}/_{4}$ ") drain valve
- 63mmdia.heavy-duty1.2mm304stainlesssteeladjustablelegsatfront and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

Controls

- Direct action thermostat reacts to + or 1.0°C
- Thermostat range 145 195°C
- Over-temperature safety cut-out
- Millivolt gas valve system (no electrical supply)
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

Cleaning and Servicing

- Open stainless steel pan for easy clean
- Easy clean basket support bar
- \bullet 32mm (1 $^{1}/_{4}$ ") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit





VEE RAY SINGLE PAN GAS FRYER 450mm

GT45

Specifications

Production rate

31kg/hr

Pan size

Oil capacity 20L (37lbs shortening) Width 365mm Length 380mm Oil frying depth 95mm

Baskets

2 chrome plated wire baskets 140mm W x 335mm D x 145mm H Stainless steel perforated basket support plate

Burners

2 x 45MJ/hr infra-red burners

Gas power

90MJ/hr, 25kW

Gas connection

R ³/₄ (BSP) male Optional rear connection (refer specification drawing)

Dimensions

Width 450mm Depth 812mm Height 915mm Incl. splashback 1085mm

Nett weight

81kg

Packing data

0.54m3, 122kg Width 870mm Depth 495mm Height 1255mm


Gas types

Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

Options

Adjustable feet at rear Filtamax Filtration System Fish plates Extra baskets Side splash guards Joining caps Castors







MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au South Australia

Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management Standard



Cert. No. 6882

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.01.19/1620